2024 FORD MUSTANG

PRELIMINARY TECHNICAL SPECIFICATIONS



Preliminary specifications as of Sept. 22, 2022 and are subject to change. Preproduction model shown. Available starting summer 2023.

MODEL	Mustang EcoBoost	Mustang GT	Mustang Dark Horse
Construction/materials	Unitized welded steel body, aluminum hood and steel front fenders	Unitized welded steel body, aluminum vented hood and steel front fenders	Unitized welded steel body, aluminum vented hood and steel front fenders
Body style	Fastback coupe, convertible	Fastback coupe, convertible	Fastback coupe
rim level	EcoBoost, EcoBoost Premium	GT, GT Premium	Dark Horse
inal assembly location	Flat Rock, Michigan	Flat Rock, Michigan	Flat Rock, Michigan
	riai noch, wiichigan	rtat Rock, Michigan	rat Rock, Michigan
DRIVETRAIN Standard	Front-engine, Rear Wheel Drive	Front-engine, Rear Wheel Drive	Front-engine, Rear Wheel Drive
	with limited-slip differential	with limited-slip differential	with limited-slip differential
NGINE CONFIGURATION			
ingine	2.3-liter EcoBoost	5.0-liter V8	5.0-liter V8
Configuration	Port fuel direct injection turbocharged I-4	Dual port fuel direct injection V8	Dual port fuel direct injection V8
'alvetrain	DOHC, Ti-VCT	DOHC, Ti-VCT	DOHC, Ti-VCT
Block/head material	High-pressure cast aluminum block and head	Cast aluminum block and head with plasma transfer wire arc cylinder liners Steel oil pan	Cast aluminum block and head with plasma transfer wire arc cylinder liners Steel oil pan Forged connecting rods
Displacement Bore x stroke Compression ratio	137.5 cu. in. (2,300 cc) 3.30 in. x 4.0 in. (84 mm x 102 mm) 10.6:1	307 cu. in. (5,038 cc) 3.63 in. x 3.65 in. (93 mm x 92.7 mm) 12:1	307 cu. in. (5,038 cc) 3.63 in. x 3.65 in. (93 mm x 92.7 mm) 12:1
nduction	Twin scroll with overboost	Naturally aspirated with dual air boxes and throttle bodies	Naturally aspirated with dual air boxes and throttl bodies
gnition system	Distributor-less with coil-on-plug	Distributor-less with coil-on-plug	Distributor-less with coil-on-plug
Fuel delivery	Port Fuel & Direct Injection	Port Fuel & Direct Injection	Port Fuel & Direct Injection
Engine control system	Powertrain control module	Powertrain control module	Powertrain control module
RANSMISSION			
Standard 6-speed manual with rev- matching and no-lift-shift	N/A	Getrag MT-82	Tremec TR-3160
Gearratios:			
st	-	3.237:1	3.25:1
nd	-	2.104:1	2.23:1
rd	-	1.422:1	1.61:1
th	-	1.000:1	1.24:1
ith	-	0.814:1	1.00:1
ith	-	0.622:1	0.63:1
0-speed automatic	Standard with optional SelectShift	Optional with standard SelectShift	Optional with standard SelectShift
st	4.696:1	4.696:1	4.70:1
nd	2.985:1	2.985:1	2.99:1
rd	2.146:1	2.146:1	2.15:1
th	1.769:1	1.769:1	1.77:1
th	1.520:1	1.520:1	1.52:1
th	1.275:1	1.275:1	1.28:1
th	1.000:1	1.000:1	1.00:1
th	0.854:1	0.854:1	0.85:1
th .	0.689:1	0.689:1	0.69:1
Oth	0.636:1	0.636:1	0.64:1
inal drive	3.15:1 Limited-slip rear axle, 3.55:1 TORSEN Limited- slip rear axle (Performance Package)	3.15:1, 3.55:1 Limited-slip rear axle, 3.55:1 TORSEN Limited-slip rear axle (Performance Package with automatic), 3.73 TORSEN Limited-slip rear axle (Performance Package with manual)	3.55:1 TORSEN Limited-slip rear axle (with automa 3.73:1 TORSEN Limited-slip rear axle (with manual)
CHASSIS/SUSPENSION	Mustang EcoBoost	Mustang GT	Mustang Dark Horse
Construction	Fully unitized steel chassis with fully independent from all convertible models, Performance Packages and	nt/rear suspension and perimeter subframe, tower-to-to lany model with 20-in. or larger wheels.	ower brace for Performance Packages. K-brace includ
	Double-ball-joint MacPherson strut with stabilizer	Double-ball-joint MacPherson strut with stabilizer bar and aluminum control arms. MagneRide dampers	Double-ball-joint MacPherson strut with stabilizer bar and aluminum control arms. MagneRide dampe
ront configuration	bar and aluminum control arms. MagneRide dampers optional on Performance Packages	optional on Performance Packages	standard
<u> </u>	bar and aluminum control arms. MagneRide dampers		standard Integral-link independent with coil springs and stabilizer bar. MagneRide dampers standard.
Pear configuration	bar and aluminum control arms. MagneRide dampers optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages	optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages	Integral-link independent with coil springs and stabilizer bar. MagneRide dampers standard.
Rear configuration TABILIZER BAR DIAMETERS	bar and aluminum control arms. MagneRide dampers optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on	optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on	Integral-link independent with coil springs and
Rear configuration TABILIZER BAR DIAMETERS Coupe	bar and aluminum control arms. MagneRide dampers optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages	optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages	Integral-link independent with coil springs and stabilizer bar. MagneRide dampers standard.
Front configuration Rear configuration STABILIZER BAR DIAMETERS Coupe Convertible Coupe Performance Package	bar and aluminum control arms. MagneRide dampers optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages 32 mm front x 21.7 mm rear	optional on Performance Packages Integral-link independent with coil springs and stabilizer bar. MagneRide dampers optional on Performance Packages 32 mm front x 21.7 mm rear	Integral-link independent with coil springs and stabilizer bar. MagneRide dampers standard. 33.3 mm front x 24 mm rear



STEERING	Mustang EcoBoost	Mustang GT	Mustang Dark Horse
Туре	Selectable-Effort Electric Power Assisted (EPAS)	Selectable-Effort Electric Power Assisted (EPAS)	Selectable-Effort Electric Power Assisted (EPAS)
туре	Selectable-Enort Electric Fower Assisted (EFAS)	Selectable-Enort Electric Fower Assisted (EFAS)	Selectable-Lifort Electric Fower Assisted (EFAS)
Steering modes	Normal, comfort, sport	Normal, comfort, sport	Normal, comfort, sport
Ratio	15.5:1	15.5:1	15.5:1
Active features	Optional MagneRide damping system	Optional MagneRide damping system	MagneRide damping system
BRAKES			
Туре	Four-wheel power disc brakes with EPB and Electronic Brake Booster and four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control; drift brake (Performance Package)	Four-wheel power disc brakes with EPB and Electronic Brake Booster and four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control; drift brake (Performance Package)	Four-wheel power disc brakes with EPB and Electronic Brake Booster and four-sensor, four-channel antilock braking system and AdvanceTrac electronic stability control; standard drift brake
Front brake configuration/ diameter/thickness/material	Standard: 320 x 30 mm vented disc, twin-piston 43 mm floating aluminum calipers; Optional: 390 x 36 mm vented discs, Brembo six-piston 36 mm fixed aluminum calipers	Standard: 352 mm x 32 mm vented discs, four-piston 46 mm fixed aluminum calipers; Optional: 390 x 36 mm vented discs, Brembo six- piston 36 mm fixed aluminum calipers	390 x 36 mm vented two-piece discs, Brembo six- piston 36 mm fixed aluminum calipers
Rear brake configuration/ diameter/thickness/material	Standard: 320 x 12 mm solid discs, single-piston 41 mm floating aluminum calipers Optional: 355 x 28 mm vented discs, four-piston 30 mm fixed aluminum calipers	Standard: 350 x 26 mm vented discs, single-piston 45 mm floating aluminum calipers Optional: 355 x 28 mm vented discs, four-piston 30 mm fixed aluminum calipers	Standard: 355 x 28 mm vented discs, four-piston 30 mm fixed aluminum calipers
Pad Material	Standard: NAO Optional: Low-metallic	Standard: NAO Optional: Low-metallic	Low-metallic
Front swept area	Standard: 467 sq. cm/plate Optional: 768 sq. cm/plate	Standard: 576 sq. cm/plate Optional: 768 sq. cm/plate	768 sq.cm/plate
Rear swept area	Standard: 402 sq. cm/plate Optional: 523 sq. cm/plate	Standard: 509 sq. cm/plate Optional: 523 sq. cm/plate	523 sq. cm/plate
SAFETY/CONTROL SYSTEMS			
ABS/stability control	ABS with AdvanceTrac	ABS with AdvanceTrac	ABS with AdvanceTrac
Airbags	Driver and passenger front, seat side, and knee airbags, side curtain (fastback only)	Driver and passenger front, seat side, and knee airbags, side curtain (fastback only)	Driver and passenger front, seat side, and knee airbags, side curtain (fastback only)
WHEELS			
Standard wheelTire dimensions	• 17 in. x 7.5 in. 235/55R	• 18 in. x 8.5 in. 255/45R W A/S	 (front) 19 in. x 9.5 in. 255/40R and (rear) 19 in. x 10 in. 275/40R (summer-only tires)
Optional	18 in. x 8.0 in. 235/50R W A/S; 19 in. x 8.5 in. 255/40R W A/S; 20 in. x 9.0 in. 265/35R W A/S; Performance Package: 19 in. x 9.0 in. 255/40R Y (summer-only tires)	19 in. x 8.5 in. 255/40R W A/S; 20 in. x 9.0 in. 265/35R W A/S; Performance Package (front) 19 in. x 9.0 in. 255/40R, (rear) 19 in. x 9.5 in. 275/40R Y (summeronly tires)	Handling Package: (front) 19 in. x 10.5 in. 305/30R and (rear) 19 in. x 11 in. 315/30R (summer-only tires)
EXTERIOR DIMENSIONS (inches unless otherwise noted)	Mustang EcoBoost	Mustang GT	Mustang Dark Horse
Wheelbase	107	107	107
Overall length	189.4	189.4	189.7
Overall width including mirrors	81.9	81.9	81.9
Overall width without mirrors	75.4	75.4	75.5
Overall height, fastback	55	55	55.2
Overall height, convertible	54.8	54.8	-
Track width, front	62	62	62.2
Track width, rear	64.7	64.7	63.9
Est. curb weight, fastback manual	N/A	N/A	N/A
Est. curb weight, fastback automatic	N/A	N/A	N/A
Est. curb weight, convertible manual	N/A	N/A	N/A
Fot and maight convertible contendation	NI/A	AL/A	NI /A

N/A

N/A

Est. curb weight, convertible automatic



INTERIOR DIMENSIONS (inches unless otherwise noted)			
Seating capacity	Four	Four	Four
Front headroom	37.6	37.6	37.6
Front headroom, convertible	37.6	37.6	_
Front legroom, SAE	44.5	44.5	44.5
Front shoulder room	56.3	56.3	56.3
Front hip room	54.9	54.9	54.9
Rear headroom, fastback	34.8	34.8	34.8
Rear headroom, convertible	35.7	35.7	-
Rear legroom, SAE fastback	29	29	29
Rear legroom, SAE convertible	29.2	29.2	-
Rear shoulder room, fastback	52.2	52.2	52.2
Rear shoulder room, convertible	44.6	44.6	-
Rear hip room, fastback	47.4	47.4	47.4
Rear hip room, convertible	43.7	43.7	-
Passenger volume, fastback	82.8 cu. ft.	82.8 cu. ft.	82.8 cu. ft.
Passenger volume, convertible	79.2 cu. ft.	79.2 cu. ft.	-
Trunk volume, fastback	13.3 cu. ft.	13.3 cu. ft.	13.3 cu. ft.
Trunk volume, convertible	10.3 cu.ft.	10.3 cu. ft.	-
HEADLIGHTS			
LED	Standard	Standard	Standard
LED Auto on/off	Standard Standard	Standard Standard	Standard Standard
Auto on/off	Standard	Standard	Standard
Auto on/off LED daytime running lamps	Standard Standard	Standard Standard	Standard Standard
Auto on/off LED daytime running lamps Auto high beam	Standard Standard Standard	Standard Standard Standard	Standard Standard
Auto on/off LED daytime running lamps Auto high beam TECHNOLOGY	Standard Standard Standard Mustang EcoBoost Six driver selectable drive modes: normal,	Standard Standard Standard Mustang GT Six driver selectable drive modes: normal, sport, slippery, track, drag strip, custom acceleration timer, brake performance, lap timer,	Standard Standard Standard Mustang Dark Horse Six driver selectable drive modes: normal, sport, slippery, track, drag strip, custom acceleration timer, brake performance, lap timer,
Auto on/off LED daytime running lamps Auto high beam TECHNOLOGY Available drive modes	Standard Standard Standard Mustang EcoBoost Six driver selectable drive modes: normal, sport, slippery, track, drag strip, custom Acceleration timer, brake performance, lap timer, performance shift indicator (manual only), drift brake, line lock, launch control (manual only), rev match	Standard Standard Mustang GT Six driver selectable drive modes: normal, sport, slippery, track, drag strip, custom acceleration timer, brake performance, lap timer, performance shift indicator (manual only), drift brake, line lock, launch control (manual only), rev match (manual only) SYNC® 4 Technology, Available B&O® Sound System	Standard Standard Mustang Dark Horse Six driver selectable drive modes: normal, sport, slippery, track, drag strip, custom acceleration timer, brake performance, lap timer, performance shift indicator (manual only), drift brake, line lock, launch control (manual only), rev match (manual only) SYNC® 4 Technology, Available B&O® Sound System

Available general

Available Intelligent Adaptive Cruise Control with Stop-and-Go and Speed Sign Recognition, Voice-Activated Touchscreen Navigation System with Pinchto-Zoom Capability, SiriusXM Traffic and Travel Link*

Available Intelligent Adaptive Cruise Control with Stop-and-Go and Speed Sign Recognition, Voice-Activated Touchscreen Navigation System with Pinchto-Zoom Capability, SiriusXM Traffic and Travel Link*

Available Intelligent Adaptive Cruise Control with Stop-and-Go and Speed Sign Recognition, Voice-Activated Touchscreen Navigation System with Pinchto-Zoom Capability, SiriusXM Traffic and Travel Link*

Available Intelligent Adaptive Cruise Control with Stop-and-Go and Speed Sign Recognition, Voice-Activated Touchscreen Navigation System with Pinchto-Zoom Capability, SiriusXM Traffic and Travel Link*

