



Specifications

Lubricants, Fluids, Sealers and Adhesives

	Specifications
Motorcraft® DOT 4 LV High Performance Motor Vehicle Brake Fluid / PM-20	WSS-M6C65-A2

Torque Specifications

Item	Nm	lb-ft	lb-in
Front caliper bleeder screw-vehicles with 2 piston brake caliper	11	-	97
Front caliper bleeder screw-vehicles with 4 piston brake caliper	8	-	71
Front caliper bleeder screw-vehicles with 6 piston brake caliper	19	-	168
Rear caliper bleeder screw-all except SVT Performance Package	11	-	97
Front and rear caliper bleeder screw-SVT Performance Package	14	-	124
Master cylinder brake tube fittings	27.5	-	20

General Specifications

Item	Specification
Front brake disc minimum thickness-vehicles with 2 piston brake caliper	1.122 in (28.5 mm)
Front brake disc minimum thickness-vehicles with 4 piston brake caliper	1.201 in (30.5 mm)
Front brake disc minimum thickness-vehicles with 6 piston brake caliper	1.244 in (31.6 mm)
Front brake disc minimum thickness-SVT Performance Package	1.339 in (34 mm)
Rear brake disc minimum thickness-solid	0.390 in (9.9 mm)
Rear brake disc minimum thickness-vented	0.925 in (23.5 mm)
Rear brake disc minimum thickness-SVT Performance Package	0.945 in (24 mm)
Brake pad minimum thickness	0.118 in (3 mm)
Brake pad maximum taper wear (in any direction)	0.118 in (3 mm)

