

(REAR - continued)

p 2 of 2

Camber — (V8 - Performance Package Level 2)	-1.14° ± 0.75°	-1.14° ± 0.75°	—
Camber — (GT350)	-1.20° ± 0.75°	-1.20° ± 0.75°	—
Camber — (GT350R)	-1.20° ± 0.75°	-1.20° ± 0.75°	—
Toe — (All Models Except, GT350, GT350R, V8 - Performance Package Level 2)	0.12° ± 0.20°	0.12° ± 0.20°	0.23° ± 0.20°
Toe — (V8 - Performance Package Level 2)	0.15° ± 0.20°	0.15° ± 0.20°	0.30° ± 0.20°
Toe — (GT350, GT350R)	0.15° ± 0.20°	0.15° ± 0.20°	0.30° ± 0.30°

### Ride Height

**NOTE:** Measurements listed at curb load. Curb load is defined as "full service fluids, full fuel tank(s), no passengers and no cargo".

Item	Specification
<b>Front Ride Height</b>	
All Models — (Except, GT350, GT350R)	48.8 mm (1.921 in) ± 12 mm (0.472 in)
GT350	35.2 mm (1.386 in) ± 12 mm (0.472 in)
GT350R	43.1 mm (1.696 in) ± 12 mm (0.472 in)
<b>Rear Ride Height</b>	
All Models — (Except, GT350, GT350R)	32.1 mm (1.264) ± 10 mm (0.394 in)
GT350	27.4 mm (1.078) ± 10 mm (0.394 in)
GT350R	18.9 mm (0.744) ± 10 mm (0.394 in)

### Vehicle Lean Side-To-Side Differences

Front — Maximum	7.5 mm (0.295 in)
Rear — Maximum	6.3 mm (0.248 in)

### General Specifications

--	--