

BRAKE FLUID



PENTOSIN DOT 4 LV

Low Viscosity/Cold Conditions Brake Fluid

DESCRIPTION

Pentosin DOT 4 LV is a special brake fluid of highest DOT 4 performance levels and extremely low viscosity at cold temperatures.

It offers safety against vapor lock; it has excellent resistance to absorbing and retaining water and provides superior corrosion resistance. Pentosin DOT 4 LV Brake Fluid is ideal for all modern vehicles with ESP and ABS. DOT 4 LV can be used in all vehicles that require DOT 4 fluid.

PRODUCT ATTRIBUTES

Appearance	Yellow & Clear
Density at 20°C	1062 kg/m ³
Kinematic Viscosity at 40°C	6.4 mm ² /s
Kinematic Viscosity at -40°C	< 700 mm ² /s
Melting Point	>-50°C/>-58°F
Flash Point	>130°C/>266°F
Ignition Temperature	>200°C/>392°F
Boiling Point	≥265°C/≥509°F
Wet Boiling Point	≥170°C/≥338°F
pH Value	Slightly Alkaline

SIZE	PART NUMBER	GTIN-13
1 Liter	1224116	4008849207228
5 Liter	1224204	4008849205156

OE REFERENCE NUMBERS/RECOMMENDATIONS

Make	Reference Number
Audi/Volkswagen	B 000 750 M1 (MX)
Audi/Volkswagen	B 000 750 M2
Audi/Volkswagen	B 000 750 M3
Audi/Volkswagen	B 000 750 M7
Audi/Volkswagen	B 000 750 M9
BMW/Mini	83 13 0 139 895
BMW/Mini	83 13 0 139 896
BMW/Mini	83 13 0 139 897
BMW/Mini	83 13 0 139 898
BMW/Mini	83 13 0 139 899
BMW/Mini	83 13 0 139 902
BMW/Mini	83 13 2 184 843
BMW/Mini	83 13 9 407 864

OE REFERENCE NUMBERS/RECOMMENDATIONS CONT.

Make	Reference Number
BMW/Mini	81 22 0 142 155
BMW/Mini	81 22 0 142 156
BMW/Mini	81 22 0 146 735
GM	19299570
Saab	93165410

APPROVALS/SPECIFICATIONS

Organization Name	Specification Met
FMVSS	No. 116 DOT 4
ISO	4925 Class 6
SAE	J1704

Always consult the vehicle owner's manual to identify fluid specification requirements. MSDS available to professional repair technician upon request.

© 2015 CRP Industries Inc. Pentosin is a trade name of Deutsche-Pentosin Werke. All rights reserved.

DISCLAIMER: CRP Industries Inc. has made every effort to assure the accuracy of the information on this product data sheet. Neither CRP Industries Inc., nor its affiliates assume responsibility for any loss or damage due to any errors, omissions or manufacturing changes.

PENTODOT4LV-081215