

## 16U-65 SCT Format

Scalars	
Fuel Injector Breakpoint	0.0000084
Fuel Injector High Slope	0.0205534
Fuel Injector Low Slope	0.0421389
Fuel Injector Minimum Pulsewidth	0.0000725
Max Allowed Inj Duty Cycle	1.999
Max Allowed Inj Duty Cycle on Alcohol	2.000

Injector Comp Batt Volt Offset	
Battery_Voltage	PW_sec
15	0.000988
14	0.001048
13	0.001149
12	0.001293
11	0.001479
10	0.001707
8	0.002289
6	0.002389

Low Slope Multiplier	
DeltaP	Multiplier
60.03	1.5998
54.96	1.4542
50.03	1.3126
39.15	1.0000
30.02	0.7377
20.01	0.4501

High Slope Multiplier	
DeltaP	Multiplier
60.03	1.3048
54.96	1.2308
50.03	1.1588
39.15	1.0000
30.02	0.8667
20.01	0.7206

Breakpoint Multiplier	
DeltaP	Multiplier
60.03	1.1544
54.96	1.1169
50.03	1.0805
39.15	1.0000
30.02	0.9325
20.01	0.8584

Batt Comp Multiplier	
Pressure	Multiplier
60.03	1.0441
54.96	1.0334
50.03	1.0230
44.95	1.0115
39.15	1.0000
30.02	0.9807
20.01	0.9596